

## **Installation Instructions**

Double Skin Acrylic  
Free Standing Baths



**(tc)**  
bathrooms

To ensure that this product is installed correctly, please read the following instructions very carefully.

- **CAUTION:** Heavy Bath, risk of personal injury or product damage, care must be taken when lifting this product. We strongly advise that the installation should be done by a qualified plumber.
- Recommended tools and materials: Adjustable wrench and sheet of cardboard.
- Ensure the bath is always kept on a protective surface so as not to cause damage example, sheet of corrugated card.
- Please attach waste fitting, ensure a good silicone seal.
- Attach taps if required.
- A second fix to pipe-work may be required if not using flexi-pipes.
- Attach feet to underneath and adjust accordingly so when fitted the panel doesn't touch the floor.
- Once the bath has been turned correctly and plumbing is complete silicone between floor and panel gap.

### Double skin acrylic baths with feet

- Turn upside down onto protective surface carefully and avoid grit.
- Fasten bracing bar to underneath of bath with washers and nuts. Fasten feet to bars with bolts, washers and nuts. Hand-tighten until sure all feet are level and then tighten firmly with adjustable wrench. Carefully position the bath where required. Attach waste to the bath with good quality silicone sealant.

### Care of baths

ALWAYS FILL ACRYLIC BATHS WITH COLD WATER FIRST THEN HOT WATER.

- **Cleaning:**
  - Wipe out baths after each use with soft cloth and towel-dry.
  - For stubborn stains use a mild dish-washing soap.
  - Do not use abrasive cleaners.
  - Avoid aerosol products on the bath surface.
  - Avoid any incandescent articles and naked flames.
  - Avoid any strong chemicals especially nail varnish remover.
  - Avoid dripping taps.
- The manufacturing process used in the making of these baths may incur a degree of surface ripples and dimples. These are quite normal and will not affect the life of your bath.